

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/tapr/qihn-kl-20lo-durbal>

\* without grease nipple

female thread;  
hydraulic rod ends,  
according to  
DIN 24338



**Inner ring:**  
bearing steel, hardened, ground and  
phosphated

**Outer ring:**  
bearing steel, hardened, ground and  
polished

**Lubrication:**  
lubrication required

| order number           |                    | measurement [mm] |                |            |                |                                    |                |                |  |
|------------------------|--------------------|------------------|----------------|------------|----------------|------------------------------------|----------------|----------------|--|
| right hand thread      | left hand thread   | d                | d <sub>2</sub> | G          | d <sub>6</sub> | B                                  | C <sub>1</sub> | C <sub>2</sub> |  |
| GIHN-KL 20 L0          |                    | 20               | 47             | M 16 x 1,5 | 25,0           | 47                                 | 20             | 17             |  |
| type                   | l <sub>1</sub> min | measurement [mm] |                |            | l <sub>2</sub> | load rating<br>C <sub>0</sub> [kN] | weight<br>[kg] |                |  |
| GIHN-K / GIHN-KL 20 L0 | 23                 | 52               | 77,0           | 22         |                | 48,0                               | 0,40           |                |  |

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE