

# TAPR Stangkop GIHO-K-20DO-DURBAL - GIHO-K-20DO-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/tapr/giho-k-20do-durbal>

## GIHO-K-20DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]						
GIHO-K 20 DO*	20	24,1	55	M 14 x 1,5	25	55	16	13	17

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	α [°]	load rating C <sub>0</sub> [N]	weight [kg]	
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952500683
Binnendiameter	20 mm
Binnendiameter	0.787" inch
Buitendiameter	55 mm
Buitendiameter	2.165" inch
Dikte	13 mm
Dikte	0.512" inch
Type	TAPR
Gewicht	430 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE