

TAPR Stangkop GIHO-K-25DO-DURBAL - GIHO-K-25DO-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/tapr/giho-k-25do-durbal>

GIHO-K-25DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHO-K 25 DO			25	29,3	65	M 16 x 1,5	30	62	20	17	17

type	h ₁	l ₁	l ₂	α [°]	load rating C ₀ [N]	weight [kg]
GIHO-K / GIHO-KL 25 DO	68	23	100,5	30	7	67,0

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952500737
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	65 mm
Buitendiameter	2.559" inch
Dikte	17 mm
Dikte	0.669" inch
Type	TAPR
Gewicht	670 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE