

SA Stangkop BRTM25-00-502-DURBAL - BRTM25-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/brtm25-00-502-durbal>

BRTM25-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]							
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂
BRTM 25 -00	-502		25	M 24 x 2	29,5	64		31	22
		measurements [mm]			weight	rotational speed limit	basic load rating		
type	h	l	b ₃	α [°]	[kg]	n _{max} [min ⁻¹]	C [N]	C ₁₀ [N]	stat. C ₀ [N]
BRTM 25	94	57	30	5,0	0,596	600	24900	18500	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952506784
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	64 mm
Buitendiameter	2.52" inch
Dikte	31 mm
Dikte	1.22" inch
Type	SA
Gewicht	596 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE