

GE Stangkop BRTM30-00-501-DURBAL - BRTM30-00-501-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/brtm30-00-501-durbal>

BRTM30-00-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

liner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number			measurements [mm]						
type	size	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂
BRTM 30 -00	-501		30	M 30 x 2	34,5	70	37	25	
measurements [mm]			weight		rotational speed limit	basic load rating		stat.	
type	h	l	b ₃	α	[kg]	n _{max} [rpm]	C [N]	C ₁₀ [N]	C ₅₀ [N]
BRTM 30	110	66	35	7,5	0,912	450	32500	24850	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060468178
Binnendiameter	30 mm
Binnendiameter	1.181" inch
Buitendiameter	70 mm
Buitendiameter	2.756" inch
Dikte	37 mm
Dikte	1.457" inch
Type	GE
Gewicht	912 g
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE