


SA Stangkop
BRM20-00-502-DURBAL - BRM20-00-502-DURBAL

https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/brm20-00-502-durbal

BRM20-00-502

male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-V

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3425 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]								
Type	Right hand thread	Left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂	h
BRM 20 -00	-502		20	M 20 x 1,5	24,5	50	25	18,0	78	
measurements [mm]			weight		calculation- factors		rotational speed limit		basic load rating	
Type	l	l ₂	α [°]	[kg]	Y	Y ₀	lim. [min ⁻¹]	C [N]	dyn. C ₀ [N]	stat. C ₀ [N]
BRM 20	47	28	7,0	0,338	2,46	2,58	825	7900	3450	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507064
Binnendiameter	20 mm
Buitendiameter	50 mm
Dikte	25 mm
Type	-
Gewicht	338 g
Draad	-
Smering	-
Verpakking	-
Standaard	-

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE