

SI Stangkop

PF10-00-502-DURBAL - PF10-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/pf10-00-502-durbal>

PF10-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread;
long-term lubrication, low maintenance, shields

order number		measurements (mm)										
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃	
PF 10 -00		-502	10	15	M 8	13,0	30	13,0			9	
			measurements (mm)				weight	calculation factors	rotational speed limit	basic load rating		
type	h	l	l ₁	r	SW	α	Y	Y ₀	lim (min)	d _{yn}	C	stat. C ₀
PF 10	38	17	14,5	10	13	7,0	0,063	1,90	1,81	1225	2605	985

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507378
Binnendiameter	10 mm
Buitendiameter	30 mm
Dikte	13 mm
Type	SI
Gewicht	63 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE