

SI Stangkop

PF15-00-502-DURBAL - PF15-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/pf15-00-502-durbal>

PF15-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields



order number		measurements (mm)												
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂				
PF 15 -00		-502	15	19	M 12	17,5	40	16,5	12					
measurements (mm)		weight	calculation factors	rotational speed limit	basic load rating									
type	h	l	l ₁	l ₂	l ₃	r	SW	α	Y	Y ₀	lim (min)	C	C ₀	stat. (N)
PF 15	51	24	20,0	15	17	7,0	0,140	2,30	2,41	1025	5000	1890		

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507385
Binnendiameter	15 mm
Buitendiameter	40 mm
Dikte	16.5 mm
Type	SI
Gewicht	140 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE