

SA Stangkop

PM05-00-502-DURBAL - PM05-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm05-00-502-durbal>


PM05-00-502



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating	
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	dyn. [N]	stat. [N]
PM 05 -00	-502	5	M 8 x 1		7,5	19	12	12	8				1350	1610	480		
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'							
PM 05		39,5	13	57	1,5	2,5	7,0	0,037									

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507439
Binnendiameter	5 mm
Buitendiameter	19 mm
Dikte	12 mm
Type	SA
Gewicht	37 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE