

SA Stangkop

PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm05-01-502-durbal>

PM05-01-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]				
type	type	type	type	type	type	type	type	type	type	type		
PM 05 -01	-502	S	M	8 x 1	7,5	19	12	12	12	8		
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		stat.		
type	type	type	type	type	type	type	type	type	type	type		
PM 05	16	13	33,5	1,5	2,5	7,0	0,033	1,51	1,58	1350	1610	480

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507446
Binnendiameter	5 mm
Buitendiameter	19 mm
Dikte	12 mm
Type	SA
Gewicht	33 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE