

SA Stangkop PM05-01-501-DURBAL - PM05-01-501-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm05-01-501-durbal>


PM05-01-501



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]						
type	type	type	type	type	type	type	type	type	type	type				
PM 05 -01	-501	S	M	8 x 1	7,5	19	12	12	12	8				
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	calculation factors Y %	rotational speed limit n _{max} [min ⁻¹]	basic load rating C [N]	stat. load rating C ₀ [N]	
PM 05	16	13	33,5	1,5	2,5	7,0			0,033	1,51	1,58	1350	1610	480

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507453
Binnendiameter	5 mm
Buitendiameter	19 mm
Dikte	12 mm
Type	SA
Gewicht	33 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE