

# SA Stangkop PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm06-02-501-durbal>


## PM06-02-501



male thread:  
long-term  
lubrication,  
low maintenance,  
shields



**DURBAL® heavy-duty rod ends  
with integral self-aligning  
ball bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-V2

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminium-complex-soap-grease,  
temperature range: -45 °C to +120 °C,  
approval according to ISO/A H1

lubrication fitting:  
DIN 3405 D1/A

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [mm]			measurements [mm]							weight		calculation factors		rotational speed limit		basic load rating	
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C	C <sub>0</sub>	C <sub>10</sub>	C <sub>010</sub>		
PM 06 -02	-501	6	M 10 x 1	8,5	24	14	14	14	10										
type		l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	u	z	α [°]										
PM 06	19	17	40,5	1,5	2,5	10,5	0,057						1,28	1,34	1300	2445	765		

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507491
Binnendiameter	6 mm
Binnendiameter	0.236" inch
Buitendiameter	24 mm
Buitendiameter	0.945" inch
Dikte	14 mm
Dikte	0.551" inch
Type	SA
Gewicht	57 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE