

SA Stangkop PM08-00-502-DURBAL - PM08-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm08-00-502-durbal>

PM08-00-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]		
type	type	type	type	type	type	type	type	type	type	type
PM 08 -00	-502	8	M 12 x 1,5	11,0	30	17	15	10		
type		measurements [mm]			weight	calculation- factors	rotational speed limit	basic load rating	dyn.	stat.
PM 08		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'
		46,5	20	72	2,0	2,5	8,5	0,097	1,9	1,81
									1225	2605
									985	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507514
Binnendiameter	8 mm
Buitendiameter	30 mm
Dikte	15 mm
Type	SA
Gewicht	97 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE