

# SA Stangkop PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm08-02-502-durbal>


## PM08-02-502



male thread:  
long-term  
lubrication,  
low maintenance,  
shields



**DURBAL® heavy-duty rod ends  
with integral self-aligning  
ball bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminium-complex-soap-grease,  
temperature range: -45 °C to +120 °C,  
approval according to USDA H1

lubrication fitting:  
DIN 3405 D1/A

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]				
type	type	type	type	type	type	type	type	type	type	type		
PM 08 -02	-502	8	M 12 x 1.5	11,0	30	17	15	10				
measurements [mm]		weight		rotational speed limit		basic load rating		stat.		stat.		
type	type	type	type	type	type	type	type	type	type	type	type	
PM 08	23	20	48,5	2,0	2,5	8,5	0,088	1,9	1,81	1225	2605	985

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507521
Binnendiameter	8 mm
Buitendiameter	30 mm
Dikte	15 mm
Type	SA
Gewicht	88 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE