

SA Stangkop

PM15-00-502-DURBAL - PM15-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm15-00-502-durbal>

PM15-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating			
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]	stat. C0 [N]	
PM 15 -00	-502	15	M 20 x 1,5	18,5	42	26	20	14									
type		l1	l2	l3	h1	h2	u	z	alpha	alpha prime							
PM 15		62,5	30	100	3,0	2,5	6,5				0,310		2,07	2,17	975	5485	3270

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507637
Binnendiameter	15 mm
Buitendiameter	42 mm
Dikte	20 mm
Type	SA
Gewicht	310 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE