

SA Stangkop

PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]							
type	type	type	type	type	type	type	type	type	type	type					
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16							
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		stat.					
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	α' [°]	[kg]	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 17	62,5	36	105	3,5	2,5	7,0	0,401			2,35	2,46		875	5575	2680

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507675
Binnendiameter	17 mm
Buitendiameter	48 mm
Dikte	22 mm
Type	SA
Gewicht	401 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE