

SA Stangkop

PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/sa/pm17-01-502-durbal>

PM17-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]		
type	type	type	type	type	type	type	type	type	type	type
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16		
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating		stat.			
type	l ₁ l ₂ l ₃ h ₁ h ₂ u z α α'	[kg]	Y γ	n _{max} [min ⁻¹]	C	C ₀	[N]	[N]	C ₀	[N]
PM 17	36 36 78,5 3,5 2,5 7,0	0,354	2,35 2,46	875	5575	2680				

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507682
Binnendiameter	17 mm
Buitendiameter	48 mm
Dikte	22 mm
Type	SA
Gewicht	354 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE