

Kogellager enkele rij 3006-SC-NICE - 3006-SC-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/3006-sc-nice>

3000 Series® Semi-Ground Radial Bearings NICE®

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3006™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.50 -0.015 0.9063 23.020

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	300 1358	300 1355	0.04 0.02	0.517 13.13	0.778 19.76	0.015 0.38

⓪ Weights given are for greased and sealed versions
⓪ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952558233
Binnendiameter	9.525 mm
Buitendiameter	23.02 mm
Dikte	7.938 mm
Gewicht	20 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE