

Kogellager enkele rij 3016-SC-NICE - 3016-SC-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/3016-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3016™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
						0.5000 12.700	1.1250 28.575

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3750 9.525	600 2670	475 2114	0.06 0.03	0.622 15.80	1.014 25.76	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3016 and larger +0.0005/-0.005 (+0.002/-0.13)

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952558431
Binnendiameter	12.7 mm
Buitendiameter	28.575 mm
Dikte	9.525 mm
Gewicht	30 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE