

## Kogellager enkele rij 3038-DC-NICE - 3038-DC-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/3038-dc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3038™	DC					+0.005 +0.13 -0.000 -0.00	+0.000 +0.50 -0.005 -0.013
						0.7500 19.050	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.9625 14.288	1480 6588	1350 6008	0.32 0.15	0.988 25.10	1.760 44.70	0.035 0.89

Ⓢ Weights given are for greased and sealed versions  
Ⓣ 3038 and larger +.0000/-0.005 (+.000/-0.13)

## PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952558844
Binnendiameter	19.05 mm
Buitendiameter	50.8 mm
Dikte	14.288 mm
Gewicht	150 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE