

Kogellager enkele rij 7508-DL-NICE - 7508-DL-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/7508-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings NICE

- PRECISION GRINDING ON ALL CONTACT SURFACES - OPTIMIZED TO THE END USER'S APPLICATION
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAXIMUM SPEEDS - HIGH RPM
- THROUGH HARDENED BEARING STEEL
- REFINED FINISH
- WIDE RETAINING FEATURES
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE RANGE - UP TO CONTACT BILLS WITH THERMALLY STABLE
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS MEET A FULL ISO 9001 CERTIFIED FACTORY MANUFACTURED TO ISO 9001
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7508™	+0.000 -0.005 -0.013	+0.000 -0.005 -0.013	+0.000 -0.005 -0.013	0.025 1.58	7500 19.05	1.009 25.63

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
G (in) (mm)	H (in) (mm)	J (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.136 3.45	0.042 1.07	1.9219 48.82	0.035 0.89	8595 11548	0.33 4581	0.750 19.05	1.500 38.10	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7514™ and larger is +0.000/-0.006 (+.000/-0.15)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FBC NICE® Bearings.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473271
Binnendiameter	12.7 mm
Buitendiameter	44.45 mm
Dikte	15.88 mm
Gewicht	150 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE