

## Kogellager enkele rij 400-36V-NICE - 400-36V-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/400-36v-nice>



- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	36V	0.700 19.05 +0.000/-0.005	1.780 44.45 +0.035/-0.000	0.562 14.27 +0.010/-0.010	0.562 14.27 Reference	14	1/4

  

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.22 0.10	625 2781	430 1914	300 1335	240 1068	188 748	117 521

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

## PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560151
Binnendiameter	19.05 mm
Buitendiameter	44.45 mm
Dikte	14.27 mm
Gewicht	100 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE