


Kogellager enkele rij 609-V-NICE - 609-V-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/609-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS SLOTS FOR SHIMMING
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
609™	V	1.000 25.40	1.075 27.31	1.719 43.70	.630 16.00	12 3/8	0.30 0.14

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1706 7592	1378 6132	1017 4520	551 2452	398 1771	284 1264

Notes
Balls - Carbon Steel Grade 52100
Washers - Carbon Steel Case Hard
Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560434
Binnendiameter	25.4 mm
Buitendiameter	50.8 mm
Dikte	16 mm
Gewicht	140 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE