


Kogellager enkele rij 616-V-NICE - 616-V-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/616-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- POLY-STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



| BEARING DIMENSIONAL DATA | | | | | | | |
|--------------------------|--------|----------------------------|-------------------|-------------------|---------------------|------------|-------------|
| BEARING | SUFFIX | A | A1 | B | C | BALLS | WEIGHT |
| | | BORE (in) (mm) | BORE (in) (mm) | O.D. (in) (mm) | HEIGHT (in) (mm) | | |
| 616™ | V | +0.010-0.000 +0.25-0.00 | +0.010 +0.25 | +0.010 +0.25 | +0.010 +0.25 | 23 | 0.4 0.18 |
| | | 1.25 31.75 | 1.275 32.35 | 2.1102 53.53 | 0.25 15.88 | 14 6.35 | |

| THRUST CAPACITY | | | | | |
|------------------------|-------|-------|-------|-------|-------|
| REVOLUTIONS PER MINUTE | | | | | |
| 10 | 50 | 100 | 250 | 500 | 1000 |
| (lbs) | (lbs) | (lbs) | (lbs) | (lbs) | (lbs) |
| (N) | (N) | (N) | (N) | (N) | (N) |
| 1794 | 1449 | 1069 | 579 | 419 | 298 |
| 7983 | 6448 | 4757 | 2577 | 1885 | 1328 |

Notes
Balls - Carbon Steel Grade 52100
Washers - Carbon Steel Case Hard
Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | NICE |
| N° Ean13 | 3663952560496 |
| Binnendiameter | 31.75 mm |
| Buitendiameter | 59.53 mm |
| Dikte | 15.88 mm |
| Gewicht | 180 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE