

Kogellager enkele rij 501-NICE - 501-NICE

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/501-nice>

500 Series® Single Row Unground Combination Radial and Thrust Bearings **NICE**

- ANGULAR CONTACT UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY

BEARING	BEARING DIMENSIONAL DATA							COMBINED RADIAL				
	A	B	C	D	E	R	BALLS No. Size	WEIGHT (lbs) (kg)	REVOLUTIONS PER MINUTE			
	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)			10	50	100	250
501™	0.250 6.35	0.687 17.45	0.250 6.35	0.219 5.56	0.500 12.70	0.094 2.38	11 1.8	0.01 0.00	72 305	48 214	50 223	33 147

AND THRUST CAPACITY						THRUST CAPACITY					
REVOLUTIONS PER MINUTE						REVOLUTIONS PER MINUTE					
100	250	500	1000	10	50	100	250	500	1000		
R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)		
36	23	23	15	16	11	10	7	71	58		
156	102	102	67	71	49	45	31	316	258		

• Maximum fillet radius on shaft which the bearing will clear

Notes
Balls - Carbon Steel Grade 200
Rings - Carbon Steel, Case Hardened
Bands - 1010 Carbon Steel, Sulf
Bearings supplied prelubricated with grease

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560533
Binnendiameter	6.35 mm
Buitendiameter	17.45 mm
Dikte	6.35 mm
Gewicht	1 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE