

## Lagerblok 2 bevestigingen N6910-B-NICE - N6910-B-NICE

<https://www.123kogellager.nl/kogellager-behuizing/lagerbloken/lagerblok-2/n6910-b-nice>

**6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing** **NICE**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 3000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO BEZEL EDGES
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

When Ordering specify whether assembly of bearing only is required.  
Bearings are stamped with designation and suffix for example 6900-12B. Housing is stamped with suffix numbers.  
Tolerance for 6912 and larger is  $\pm 0.000$  to  $\pm 0.001$ .

BEARING		PRINCIPLE DIMENSIONS					
FLANGED UNIT	BEARING ONLY	Bore d (in)	O.D. D (in)	Width B (in)	Width E (in)	E (in)	F (in)
	SUFFIX	+0.005	+0.000	+0.000			
		-0.005	+0.000	+0.000			
N6910™	B	0.625	1.6250	0.500	1.000	0.985	0.500
		15.875	41.28	12.70	25.40	24.98	12.70

### PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473363
Schachtdiameter	15.875 mm
Aantal bevestigingsmiddelen	2
Aanscherping	borgschroef
Bevestigingsmiddelpuntafstand	73.03 mm
Materiaal	TOLE
Gewicht	150 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE