

Lagerbloken toebehoren 7612-DL-NICE - 7612-DL-NICE

<https://www.123kogellager.nl/kogellager-behuizing/lagerbloken/toebehoren/7612-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE™

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE TIGHT BEARING
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHOULD BE OILED
- SEALY APPLICABLE SINGLE LIP CONTACT ONLY
- AVAILABLE SINGLE SEALER OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS WILL ENHANCE LIFE IN OPTION
- INDICATED FOR APPLICATIONS WHERE EXCESSIVE VIBRATION AND SHOCK ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
	+0.0008 +0.020 -0.0000 -0.001	+0.0000 +0.005 -0.0005 -0.013	+0.000 +0.005 -0.005 -0.13	+0.000 +0.005 -0.005	+0.005 +0.005 -0.005	+0.005 +0.13 -0.005 -0.13
7612™	.7500 19.05	1.7500 44.54	0.6250 15.88	0.0625 1.59	1.000 25.40	0.136 3.46

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (kg)
0.042 1.07	1.922 48.82	1.982 50.33	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2996 11548	1025 4061	0.28 0.13

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7612™ and larger is +0.0005-0.0006 (+0.0005-0.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC NICE® Bearings.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473431
Binnendiameter	19.05 mm
Buitendiameter	25.63 mm
Dikte	15.88 mm
Gewicht	130 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE