

Lagerbloken toebehoren N6906-NICE - N6906-NICE

<https://www.123kogellager.nl/kogellager-behuizing/lagerbloken/toebehoren/n6906-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

EASY TO USE DIMENSIONS

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALER STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY SUFFIX	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
N6906™	B	0.375 9.53	0.9063 23.02	0.313 7.94	0.688 17.46	0.555 14.10	0.375 9.53	1.875 47.63	2.500 63.50

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT	
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C ₀ (lbs) (N)	W (lbs) (kg)
1.125 28.58	0.344 8.73	0.344 8.73	0.688 17.46	0.035 0.89	8-32	0.3125 7.94	0.020 0.50	580 2581	300 1335	0.07 0.03

① When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6906™B. Housings no longer carry part numbers.
② Tolerance for 8912 and larger is +.0001/-0.0006 (+000/-016) ③ Weights given are for greased and sealed version with flange mount.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952564784
Binnendiameter	9.53 mm
Buitendiameter	23.02 mm
Dikte	7.94 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE