

Lagerbloken toebehoren N6910-NICE - N6910-NICE

<https://www.123kogellager.nl/kogellager-behuizing/lagerbloken/toebehoren/n6910-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

EASY TO USE DIMENSIONS

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED HOUSING
- NYLON RETAINER STANDARD
- SHOULDER BEARING STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
	SUFFIX	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.005 -0.01	+0.000 +0.00 -0.002 -0.15					
N6910™	B	0.625 15.875	1.6250 41.28	0.500 12.70	1.000 25.40	0.955 24.26	0.500 12.70	2.875 73.03	3.750 95.25

PRINCIPLE DIMENSIONS								BASIC LOAD RATINGS		WEIGHT
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C ₀ (lbs) (N)	W (lbs) (kg)
1.875 47.63	0.438 11.11	0.688 17.48	1.000 25.40	0.062 1.57	1/4-28	0.4375 11.11	0.010 0.25	1610 7165	1010 4485	0.32 0.15

① When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.
② Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) ③ Weights given are for greased and sealed version with flange mount.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473660
Binnendiameter	15.875 mm
Buitendiameter	41.28 mm
Dikte	12.7 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE