

Lagerbloken toebehoren N6916-NICE - N6916-NICE

<https://www.123kogellager.nl/kogellager-behuizing/lagerbloken/toebehoren/n6916-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

EASY TO USE DIMENSIONS

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALER STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
		+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.005 -0.01	+0.000 +0.00 -0.002 -0.15					
N6916™	B	1.000 25.40	2.000 50.80	0.583 14.29	1.063 26.99	1.293 32.84	0.500 12.70	3.250 82.55	4.125 104.78

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT	
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C ₀ (lbs) (N)	W (lbs) (kg)
2.250 57.15	0.438 11.11	0.688 17.48	1.125 28.58	0.062 1.57	10-32	0.4375 11.11	0.062 1.57	1870 8322	1350 6008	0.33 0.15

① When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.
 ② Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) ③ Weights given are for greased and sealed version with flange mount.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952564814
Binnendiameter	25.4 mm
Buitendiameter	50.8 mm
Dikte	14.29 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE