

TSM Stangkop MS-05-4F-DUNLOP - MS-05-4F-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/tsm/ms-05-4f-dunlop>

MALE ROD ENDS 



MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 52100/79 and forged 6061Al, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 52100/20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 150Cr6 heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +250°C

Specification:
ELV & RoHS compliant

Housing: Steel 52100/79 (Sizes 04 - 07) Forged 6061Al (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 52100/20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 150Cr6, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|----------|-------|-------|-------|-------|-------|-------|-------------------------------------|
| MS-05-4F | | 1/4 | 5/16 BSF | 0.437 | 0.344 | 1.000 | 1.875 | 1.250 | 11.35 | 11,100 |

Interchange table

| Dunlop | Rose | Aurora | Askubal | SKF | ASAHI | IKO | Fluro |
|---------------|------|-------------------|---------|--------|--------|---------|-------|
| MS-M (metric) | MHC | MM-M-T and MB-M-T | KA-P | SAKB-P | JAM-EC | POS-EC | GASW |
| MS (imperial) | RMC | MM-T and MB-T | - | - | - | POSB-EC | - |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04-SS'

MALE ROD ENDS

MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 52100/79 and forged 6061Al, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 52100/20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 150Cr6 heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +250°C

Specification:
ELV & RoHS compliant

Housing: Steel 52100/79 (Sizes 04 - 07) Forged 6061Al (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 52100/20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 150Cr6, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|----------|-------|-------|-------|-------|-------|-------|-------------------------------------|
| MS-05-4F | | 1/4 | 5/16 BSF | 0.437 | 0.344 | 1.000 | 1.875 | 1.250 | 11.35 | 11,100 |

Interchange table

| Dunlop | Rose | Aurora | Askubal | SKF | ASAHI | IKO | Fluro |
|---------------|------|-------------------|---------|--------|--------|---------|-------|
| MS-M (metric) | MHC | MM-M-T and MB-M-T | KA-P | SAKB-P | JAM-EC | POS-EC | GASW |
| MS (imperial) | RMC | MM-T and MB-T | - | - | - | POSB-EC | - |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04-SS'

PRODUCTKENMERKEN

| | |
|---------------------|---------------|
| Merk | DUNLOP |
| N° Ean13 | 3616060549389 |
| Binnendiameter | 6.35 mm |
| Buitendiameter | 25.4 mm |
| Dikte | 11.0998 mm |
| Type | TSM |
| Draad | Rechtse draad |
| Smering | met |
| Statische belasting | 0.0111 kN |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE