

SI Stangkop FXL-M16-G-DUNLOP - FXL-M16-G-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/fxl-m16-g-dunlop>

FEMALE ROD ENDS DUNLOP

DUNLOP
FEMALE ROD ENDS

FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, heat treated to 80/90 tons/in² tensile, phosphated all over. **Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FXL-M16G		16	22.2	19.0	22.2	49.2	66.7	34.0	25.4	M16 x 2.00	21	77470

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060555199
Binnendiameter	16 mm
Binnendiameter	0.63" inch
Buitendiameter	22.2 mm
Buitendiameter	0.874" inch
Dikte	19 mm
Dikte	0.748" inch
Type	SI
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE