

# SI Stangkop FSLX-10-8-DUNLOP - FSLX-10-8-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/fslx-10-8-dunlop>

**FEMALE ROD ENDS**



**FSX SERIES**

**Description:**  
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: 100Cr6 Heat Treated, polished and electroless Nickel plated and stainless steel 440C

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specification:**  
ELV & RoHS compliant

**Temp Range:** -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-10-8		1/2	5/8 UNF	0.750	0.542	1.750	2.500	1.500	0.875	67500

**Interchange table**

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060556202
Binnendiameter	12.7 mm
Buitendiameter	44.45 mm
Dikte	19.05 mm
Type	SI
Draad	Linkse draad
Smering	NA
Statische belasting	67.5 kN
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE