



SI Stangkop AL-SA-032-DUNLOP - AL-SA-032-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/al-sa-032-dunlop>

FEMALE ROD ENDS



FEMALE ROD ENDS



AL SERIES

Description:
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminum A6061, Black Anodized Race: GR-nylon, LV-3H
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-032		3	M3x0.50	6	4.50	12	18.5	7.0	5.2	6.5	3,040

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060556479
Binnendiameter	3 mm
Binnendiameter	0.118" inch
Buitendiameter	6 mm
Buitendiameter	0.236" inch
Dikte	4.5 mm
Dikte	0.177" inch
Type	SI
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE