



SI Stangkop AL-SA-106-DUNLOP - AL-SA-106-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/si/al-sa-106-dunlop>

FEMALE ROD ENDS



FEMALE ROD ENDS



AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminium A6061, black anodised. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminium A6061, Black Anodised Race Ball: GR-nylon, LV-3H Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | AF | Static Load Rating Radial (Newtons) |
|---------------------|--------------------|-----------|---------|---|------|----|------|-----|-----|-----|-------------------------------------|
| AL-SA-106 | | 3 | M3x0.50 | 6 | 4.50 | 12 | 18.5 | 7.0 | 5.2 | 6.5 | 3,000 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DUNLOP |
| N° Ean13 | 3616060556592 |
| Binnendiameter | 3 mm |
| Buitendiameter | 6 mm |
| Dikte | 4.5 mm |
| Type | SI |
| Draad | Rechtse draad |
| Smering | met |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE