

GE Stangkop GE12-ES-DUNLOP - GE12-ES-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge12-es-dunlop>

SPHERICAL BEARINGS 



GE ES SERIES

Description:
GE ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race riding surfaces are treated with MoS2 for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS2. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial mechanical applications
Construction equipment
Agricultural equipment
hydraulic applications

Temperature Range:
-24°C to +121°C

Specifications:
ELV & RoHS compliant



Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS2.

Balls: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE12ES		12	10	7	22	94,000

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060557476
Binnendiameter	12 mm
Binnendiameter	0.472" inch
Buitendiameter	22 mm
Buitendiameter	0.866" inch
Dikte	10 mm
Dikte	0.394" inch
Type	GE
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE