

GE Stangkop

GE212-ES-2RS-DUNLOP - GE212-ES-2RS-DUNLOP

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge212-es-2rs-dunlop>

SPHERICAL BEARINGS 



GEZ ES SERIES

Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE212ES-2RS	2-3/4	61.112	52.375	111.125	1,250,000



PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060558299
Binnendiameter	19.5 mm
Buitendiameter	61.11 mm
Dikte	52.37 mm
Type	GE
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE