

Naaldhulslager TAM3230-IKO - TAM3230-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/tam3230-iko>



| Boundary dimensions | | | Standard mounting dimensions mm | | | | | | Basic dynamic load rating | | Basic static load rating | | Allowable rotational speed | Assembled inner ring |
|---------------------|----|----|---------------------------------|--------|-------------------|--------|--------|----|---------------------------|-------|--------------------------|--|----------------------------|----------------------|
| mm | | | Shaft dia. | | Housing bore dia. | | | | C | CR | rpm | | | |
| Fw | D | C | h6 | H7 | h6 | H7 | h6 | H7 | N | N | | | | |
| 32 | 42 | 30 | 3.4 | 32.000 | 31.984 | 42.014 | 41.989 | -- | 39500 | 68400 | 11000 | | RT 2830 | |

PRODUCTKENMERKEN

| | |
|----------------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060599520 |
| Binnendiameter | 32 mm |
| Buitendiameter | 42 mm |
| Dikte | 30 mm |
| Grenstoerental | 11000 rpm |
| Dynamische belasting | 39.5 kN |
| Statische belasting | 68.4 kN |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE