

## Naaldhulslager BA1010-Z-IKO - BA1010-Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/ba1010-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(1)	Assembled inner ring
$F_w$	$B$	$C$	Shaft dia. $d$	Housing bore dia. $D$	$C$	$CV$	$C$	$C_0$	rpm	
15.875 (15.87)	20.638 (8.125)	15.88 (6.25)	15.875 (15.87)	20.638 (8.125)	15.88 (6.25)	1.3	7320	10700	25000--	

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060602961
Binnendiameter	15.875 mm
Buitendiameter	20.638 mm
Dikte	15.88 mm
Grenstoerental	25000 rpm
Gewicht	10 g
Dynamische belasting	7.32 kN
Statische belasting	10.7 kN
Verpakking	1
Standaard	Geen standaard

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE