

Naaldhulslager BA128-Z-IKO - BA128-Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/ba128-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable axial displacement	Assembled inner ring	
<i>P₀₄</i>	<i>D</i>	<i>C</i>	<i>d</i>	<i>h₀</i>	<i>d₁</i>	<i>C</i>	<i>C₀</i>	speed(l)		
Min.	Max.	Min.	Max.	Min.	Max.	Min.	N	N	rpm	
19.900	25.400	12.700	19.050	19.037	25.412	25.391	6910	8780	20000	RB 88-1

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060603166
Binnendiameter	19.05 mm
Binnendiameter	3/4" inch
Buitendiameter	25.4 mm
Buitendiameter	1" inch
Dikte	12.7 mm
Dikte	1/2" inch
Grenstoerental	20000 rpm
Dynamische belasting	6.91 kN
Statische belasting	8.78 kN
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE