

Kogellager enkele rij 71905CD-P4A-SKF - 71905CD-P4A-SKF

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/enkele-rij/71905cd-p4a-skf>

Dimensions d'encombrement		Charges de base		Vitesses admissibles		Désignation	
d	D	B	C	C ₂	Grease lubrication		Oil-air lubrication
mm	42	9	6,76	4	36000	53000	71905 CD/P4A
Ball diameter		4,762					
Number of balls		10					
Précharge hors montage [N]		900-8-000, face-à-face		Coefficients de calcul			
Classe de précharge		A B C D		For equivalent bearing load			
25 50 100 200				C ₁₀ 10,2			
Static axial stiffness [N/mm]		(grip force value)		For pretord in mounted bearing sets			
Classe de précharge		A B C D		f ₁ 1			
24 30 44 62				f _{2a} 1			
Reference grease quantity [cm ³]		G _{ref} 0,54		f _{2b} 1,04			
				f _{2c} 1,09			
				f _{2p} 1,15			
				f _{2c} 1			

PRODUCTKENMERKEN

Merk	SKF
N° Ean13	7316570235760
Binnendiameter	25 mm
Waterdicht maken	Niet waterdicht
Kooi	Niet-metaal
Contacthoek	15 °
Buitendiameter	42 mm
Dikte	9 mm
Dynamische belasting	6.76 kN
Statische belasting	4 kN
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE