

Zelfklevend

5206-300ML-LOCTITE - 5206-300ML-LOCTITE

<https://www.123kogellager.nl/lijm-smering/lijm/zelfklevend/5206-300ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Étanchéité plane, moyennement flexible
NOM	LOCTITE 5206
CONDITIONNEMENT	Cartouche 300 ml
COMMENTAIRE	
APPROBATION*	

Description

LOCTITE® 5206 is a red, viscous, fluorescent dimethacrylate ester acrylic flange sealant. It seals close fitting joints between rigid metal faces and flanges. It provides resistance to low pressures immediately after assembly. It is used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc.

Avantages

Fluorescent
Provides resistance to low pressures immediately after assembly
Used as a form-in-place gasket
May be dispensed robotically with the appropriate LOCTITE product conditioning and dispensing systems

Caractéristiques

Dimethacrylate ester flange sealant. It seals close fitting joints between rigid metal faces and flanges having immediate resistance to low pressures.

PRODUCTKENMERKEN

Merk	LOCTITE
N° Ean13	5010266266992
Type	ETANCHEITE
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE