

Kegelager 30308-XR-JTEKT - 30308-XR-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/30308-xr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
40	90	25.25	23	20	2	1.5	87.3	98.5	4 600	6 100	30308XR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
—	23.8	50	53	80	72	84	3	5	2	1.5	0.55	1.10	0.60	0.780	

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952404912
Binnendiameter	40 mm
Buitendiameter	90 mm
Dikte	25.25 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE