

# Kegellager 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.			
100	215	77.5	73	60	4	3	579	783	1 800	2 400	32320JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.		r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>
260	53.9	118	123	201	177	200	8	17.5	3	2.5	0.35	1.74	0.96	13.0

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952410623
Binnendiameter	100 mm
Buitendiameter	215 mm
Dikte	77.5 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE