

# Kegellager 32322-JTEKT - 32322-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/32322-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
110	240	84.5	80	65	607	797	1 600	2 200			32322

  

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	r <sub>1b</sub> min.	r <sub>1b</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
—	57.3	128	137	226	198	222	9	19.5	3	2.5	0.35	1.73	0.95	16.6	

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250125324
Binnendiameter	110 mm
Binnendiameter	4.331" inch
Buitendiameter	240 mm
Buitendiameter	9.449" inch
Dikte	84.5 mm
Dikte	3.327" inch
Gewicht	10270 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE