


Kegellager 30324-JTEKT - 30324-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/30324-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.			
120	260	59.5	55	46	4	3	505	611	1 500	2 000	30324

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	48.9	138	152	246	221	239	10	13.5	3	2.5	0.35	1.73	0.95	13.7

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250122491
Binnendiameter	120 mm
Binnendiameter	4.724" inch
Buitendiameter	260 mm
Buitendiameter	10.236" inch
Dikte	59.5 mm
Dikte	2.343" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE