


# Kegelager 30332-D-JTEKT - 30332-D-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegelager/30332-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. 1)
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
160	340	75	68	48	742	933	900	1300			30332D

Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	101.8	182	195	322	290	320	9	27	4	3	0.81	0.74	0.41	29.1

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952421261
Binnendiameter	160 mm
Binnendiameter	6.299" inch
Buitendiameter	340 mm
Buitendiameter	13.386" inch
Dikte	75 mm
Dikte	2.953" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE