


## Kegellager

### L44640R-L44610-JTEKT - L44640R-L44610-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegellager/l44640r-l44610-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
23.812	50.292	14.224	14.732	10.668	1.6	1.2	31.2	37.0	7 800	10 000

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg) Inner ring Outer ring	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>		
L44640R	L44610	10.8	30.5	28.5	44.5	47.0	1.6	1.2	0.37	1.60	0.88	0.099	0.034

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952425559
Binnendiameter	23.812 mm
Binnendiameter	15/16" inch
Buitendiameter	50.292 mm
Buitendiameter	1.98" inch
Dikte	14.224 mm
Dikte	0.56" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE