


Kegelager

HH224349-HH224310-JTEKT - HH224349-HH224310-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/rollager/kegelager/hh224349-hh224310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub. Oil lub.		
114.976	212.725	66.675	66.675	53.975	7.1	3.2	513	699	1 800	2 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
HH224349	HH224310	47.6	135.0	134.0	189.0	201.0	7.1	3.2	0.33	1.84	1.01	6.58	3.03

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952430416
Binnendiameter	114.9 mm
Binnendiameter	4.524" inch
Buitendiameter	212.725 mm
Buitendiameter	8 3/8" inch
Dikte	66.675 mm
Dikte	2 5/8" inch
Gewicht	9850 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE