


Naaldhulslager 5BFNM99-JTEKT - 5BFNM99-JTEKT

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/5bfnm99-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 5 | 9 | 9 | — | 2.40 | 2.15 | 44 000 | 5BFNM99 — |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|-------|-----------------------------|-------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 4.992 | 5.000 | 8.981 | 8.996 | 1.8 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952469263 |
| Binnendiameter | 5 mm |
| Buitendiameter | 9 mm |
| Dikte | 9 mm |
| Gewicht | 1.8 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE